

SOLARTRON

TRUE R.M.S. VOLTMETER VM 1483
VM 1484

TENTATIVE DATA


- * LINEAR SCALE TRUE R.M.S. READING
- * HIGH CREST FACTOR RATING
- * DC OUTPUT PROVIDES R.M.S. - AC TO DC CONVERTER WITH DIGITAL VOLTMETER READING FACILITY

VM 1483

- * VOLTAGE RANGE 100mV to 1 VOLT
- * ACCURACY 2% FROM 10c/s - 100Mc/s
0.2% AT MIDBAND FREQUENCIES
- * INPUT IMPEDANCE 50 OHMS
- * DC CALIBRATION WITH D.V.M.
MONITORING FACILITY
- * 6 VOLT CONTINUOUS OVERLOAD

VM 1484

- * 100 μ V TO 300 VOLTS IN 12 RANGES
- * ATTENUATOR WITH 10dB STEPS FROM
- 72dB TO +50dB
- * ACCURACY \pm 1% F.S.D. FROM 50c/s -
3Mc/s, \pm 5% F.S.D. 10c/s - 10Mc/s
- * INPUT IMPEDANCE 10M/20pF
- * 0.5% SQUARE WAVE CALIBRATOR
- * FULL OVERLOAD PROTECTION



SOLARTRON

SPECIFICATION VM 1484

VOLTAGE RANGES:	1mV F.S.D. to 300V F.S.D. in 12 ranges in 1, 3, 10 sequence. Scales arranged to give constant dB scale, to omit the 10dB attenuator, ranging from -72dB to +50dB. Readings down to 100 μ V can be made.
ACCURACY:	\pm 1% of F.S.D. from 50c/s to 3Mc/s \pm 5% of F.S.D. from 10c/s to 10Mc/s Useful readings at frequencies outside this range.
CREST FACTOR RATING:	8:1 at F.S.D. (Proportionately greater at fractions of F.S.D. e.g., 16:1 at half scale, 32:1 at quarter scale).
CALIBRATOR:	100mV and 1V square waves. R.M.S. values accurate to 0.5%.
INPUT IMPEDANCE:	10M Ω shunted by 20pF.
RESPONSE TIME:	Typically 3 seconds to 1% of final reading.
OVERLOAD PROTECTION:	The instrument is fully protected against overload. The limiting voltages are 450V peak on the 300V range and 600V DC on the input socket.
OUTPUT:	300mV at 0.5mA from 1K Ω source impedance on Digital Voltmeter socket (Linear Law).
AMBIENT TEMPERATURE OPERATING RANGE:	0 $^{\circ}$ C to 50 $^{\circ}$ C.
POWER REQUIREMENTS:	95-125V/190-250V 50-60c/s 14VA approx.
DIMENSIONS & WEIGHT:	
BENCH UNIT	Height 8.1/4 ins. Width 5.5/8 ins. Depth 13 ins. Weight 14 lbs.
1/3 RACK MODULE	Height 7 ins. Width 5.5/8 ins. Depth 13 ins.
ACCESSORIES AVAILABLE:	CX 1563 Probe Adaptor CX 1167 X10 Probe CX 1564 3ft. of co-axial cable with UHF plug and test prods; banana jacks, spade terminals, crocodile clips and test rods. CX 1565 Calibration lead.

We reserve the right to change specifications and prices without notice.



THE SOLARTRON ELECTRONIC GROUP LTD.

Victoria Road, Farnborough, Hants.

Telephone: Farnborough (Hants) 3000. Telex: 8545 Solartron Fnbro. Cables: Solartron Farnborough.

A MEMBER OF THE SCHLUMBERGER GROUP